

# NBM Series Mulcher



The BULLY NBM Series Mulcher is a multi-purpose implement. Its robust design makes light work of bracken, as well as prunings and undergrowth (up to 30mm).

A 2,295 rpm rotor speed, coupled with a rear opening flap, gives the operator flexibility of single cut topping or a finer mulched finish on grassy applications like paddocks and parks and gardens, regardless of the grass height.

The NBM Mulcher has two bolted mounting positions (21 cm apart) allowing the operator to offset the implement on the tractor's three-point linkage. The NBM Mulcher comes standard with hammers, height adjustable replaceable skids and a rear roller.



Code	TNBM145	TNBM155	TNBM175
Size reference	1.45m   4'9"   57"	1.55m   5'2"   61"	1.75m   5'10"   69"
Side transmission	Belt drive		
Belts	Three (3) SPAB		Four (4) SPAB
Gearbox	50hp, 540rpm with freewheel		
PTO shaft/clutch	Series 4		
Skids	Adjustable, four (4) positions		
Rear roller	Ø121mm, height adjustable, eight (8) positions		
Finish	Powder coated		
Rotor swing dia. (mm)	350mm (blade tip to blade tip diameter)		
Rotor diameter (mm)	108		
Rotor speed (rpm)	2295		
Type of blade	Hammer		
No. of hammers	24	24	28
Tower position/offset	Fixed/bolt-on with two (2) mounting positions, 210mm apart		
Linkage	Category 1		
Guarding	Standard with CE compliant, individual metal flap guarding		
Overall width (mm)	1685	1785	1985
Working width (mm)	1450	1550	1750
Cutting height (mm)	18 - 118		
Tractor range (hp)	30 - 50	35 - 50	40 - 50
Weight (kg)	355	362	376

## Parts

17530.1 Bully NBM Series hammer (each)

GB/T12732-S NBM/TSS Series belt (each)