

The European designed BULLY SFM-H Series Mulchers have a gearbox rating up to 70hp (max.). The gearbox is fitted with a built-in freewheel which allows the rotor to slowly spin to a stop in the event that the PTO power is shut off while the PTO input is at speed.

The tower of the SFM-H Mulcher is hydraulically side shifting (up to 300mm), allowing the operator to shift the mulcher in and out the side. This control is beneficial when mulching along fence lines or under tree branches and vines.

The rear of the deck has a series of removable, height adjustable mulching rakes that hold large prunings (up to \emptyset 50mm) in the cutting chamber for maximum mulching, which along with the high-speed rotor, four belt drive and hammer blades produce a high-quality cut finish in vineyards, orchards and pastures.





Farm Implements | T: +61 3 9706 5166 | E: sales@farmimplements.com.au | W: farmimplements.com.au





| Code | TSFM160H | TSFM175H | TSFM205H | TSFM220H |
|-----------------------|--|---------------------------------|---------------------|-------------------------------|
| Size reference | 1.6m 5'4" 64" | 1.75m 5'10" 69" | 2.05m 6'10" 82" | 2.2m 7'4" 88" |
| Side transmission | Belt drive | | | |
| Belts | Four (4) BX type | | | |
| Gearbox | 70hp, 540rpm with freewheel | | | |
| PTO shaft/clutch | Series 4 Series 6 | | | |
| Skids | Adjustable, three (3) positions | | | |
| Rear roller | Ø 140mm, height adjustable | | | |
| Finish | Powder coated | | | |
| Rotor swing dia. (mm) | 380 | | | |
| Rotor diameter (mm) | 160 | | | |
| Rotor speed (rpm) | 2083 | | | |
| Type of blade | Hammer standard 'Y' blades on request | | | |
| No. of hammers | 20 | 22 | 26 | 28 |
| Tower position/offset | Hydraulic side shift (300mm) | | | |
| | 770 - 830 mm 470 - 1130 mm mm | 845 905 mm 545 1205 mm mm | 995 | 1070 1030 mm 1430 mm mm |
| Linkage | Category 1 and 2 (bushes for category 2) | | | |
| Guarding | Standard with CE compliant, individual metal flap guarding | | | |
| Overall width (mm) | 1770 | 1920 | 2220 | 2370 |
| Working width (mm) | 1600 | 1750 | 2050 | 2200 |
| Cutting height (mm) | 20 - 105 | | | |
| Tractor range (hp) | 40 - 70 | 50 - 70 | 55 - 70 | 60 - 70 |
| Weight (kg) | 420 | 440 | 485 | 510 |

Parts 17228 17229

Bully SFM Series Y blade (each) Bully SFM Series Y blade spacer (each) Parts 17295 17698

Bully SFM Series hammer (each) SFM Series belt set (4 belts)

Farm Implements | T: +61 3 9706 5166 | E: sales@farmimplements.com.au | W: farmimplements.com.au