

Suitable for tractors from 30 to 60hp the KANGA MHD Grader Blade has been engineered to perform a wide range of applications. Their versatility makes them an excellent choice for levelling, finish grading and backfilling.

A tapered main beam provides the strength required to handle the adjustment this blade offers the operator; tilt (max. 24°), angle (max. 40°) and offset (max. 45°). The main pivot points are greaseable while the adjustment pin holes are all reinforced.

The mouldboards involuted design enables more efficient and continuous cutting, mixing and rolling of material while the wings help keep the material contained within the blade area.



Code	KBMHD180	KBMHD210
Size reference	1.8m 6'0" 72"	2.1m 7'0" 84"
Headstock	Tapered 6mm main beam	
Mouldboard	Reversible 8mm mouldboard	
Cutting edge	High tensile road grade, reversible	
Linkage	Category 1 and 2, double clevis pins	
Finish	High build primer and agricultural enamel topcoat	
Adjustment	Angle, offset and tilt	
Controlled by	Pins and clips	
Blade angle	5 positions = square, 2 left, 2 right 20° & 40°	
Blade offset	7 positions = square, 3 left, 3 right 15° (335mm), 30° (670mm) & 45° (1,000mm)	
Blade tilt	5 positions = square, 2 left, 2 right 12° & 24°	
Overall width (mm)	1800	2100
Tractor range (hp)	30 - 60	45 - 60
Weight (kg)	250	260