

EX SERIES

EX5310 ROPS • EX5810 ROPS

53 - 58 HP



WWW.KIOTI.COM.AU









The measure that makes a tractor a true asset is the boost it gives to your productivity. It has to deliver enough power and versatility for a wide range of applications, day in, day out, season after season. This is where Kioti's EX Series outperforms the competition and offers unbeatable value.

With two engine configurations, 53 hp and turbo-aspirated 58hp, many features give these tractors the edge over the competition, including the powerful hydraulic system flow, 12 x 12 three-range generous 3pl lift capacity of 1131 kg, standard loader with 4-in-one bucket and standard three-speed auto PTO.

The flat platform operator area has a no-slip mat, standard footactivated tilt steering column and fully adjustable deluxe suspension seat for all-day comfort. High ground speed, push button 4WD, and power steering give you confidence, traction and excellent manoeuvrability in changing ground conditions.





MAIN FEATURES

- Powerful 53 hp/58 hp engine
- Synchro shuttle transmission
- 12 x 12 speed transmission
- 62.4 LPM hydraulic pump flow
- 1,131 kg 3 PL capacity @ 610 mm
- Two sets of rear remote outlets
- Auto PTO
- 540 750 1000 PTO speeds
- Flat working platform
- Tilt steering wheel
- Deluxe suspension seat



Adjustable mechanical suspension seat making operation more comfortable.



Well placed forward/reverse shuttle lever for ease



Convenience of a 3 speed PTO, 540 750 and 1000rpm. A speed for every job.



Electronically engaged 4WD operation.



A rear lift capacity of 1131 kg. Standard with 2 sets A flat operator station, with a tilt steering column of rear hydraulic remotes.



and ergonoically placed controls.

Some images show machinery that is not included in the standard specification sale.

WHETHER YOU COMPARE SPECS AND CRUNCH THE NUMBERS YOURSELF, OR HAVE A CHAT WITH YOUR LOCAL DEALER, THE ULTRA-VERSATILE EX SERIES ADDS UP TO A GREAT CHOICE FOR A BETTER TRACTOR.







ISO 9001 NO.954596

ISO 14001 NO 771475

OHSAS 18001

SPECIFICATIONS

MODEL			EX5310	EX5810
ENGINE				
Model			4B243DM-C1	4B243DTM-C
Туре			4Cyl., In-line Vertical,Water-cooled, 4-cycle diesel engine	
Engine Max		HP	53	58
Engine Gross		HP	50	55
Rated revolution		rpm	2,600	
Displacement		CC	2,435	
Fuel Tank		L	45	
DRIVE TRAIN				
Clutch			Dry type single stage	
Transmission			Manual	
Speeds			12	
Differential Lock			Rear Standard	
Brake			Wet Disc Type	
PTO Type			Independent	
Rear PTO (Standard)		rpm	540,750,1000	
4WD Type			Electronic Actuation	
HYDRAULIC SYSTEM				
Pump			Gear	
Pump Capacity (Max. Flow Rate)		L/min	62.4	
3-Point Hitch			Category 1	
Maximum Lifiting Capacity (600mm aft. of hitch)		kg	1131	
Number of Remote Valves			2	
TIRE SIZE				
Front (AG)			9.5 - 16	
Rear (AG)			13.6 - 26	
TRAVELLING SPEEDS				
Forward		km/h	1.5~27.9	
Reverse		km/h	1.4~24.8	
DIMENSIONS				
Overall Length (includes 3-Point Hitch)		mm	3,158	
Overall Width (minimum Tread)		mm	1,675	
Overall Height		mm	2,550	
Wheelbase		mm	1919.5	
Minimum Ground Clearance		mm	405	
Tread	Front (AG)	mm	1,410	
	Rear (AG)	mm	1,324	
Minimum Turning Radius (with brake)		mm	3,130	
Weight (with ROPS)		kg	1,790	1,795

STANDARD EQUIPMENT

- 4WD
- Rear PTO
- Joystick Valve
- Horn
- Head Lamp
- Signal Lamp
- Fuel Tank Cap
- PTO Cover

OPTIONAL EQUIPMENT

- Front Weight
- Rear Weight
- Rear View Mirror
- 7 Pin Socket
- Rear Work Light
- Sun Canopy
- Front Grille Guard

^{*}Note: The specifications are subject to change for the purpose of improvement without any notice.